


```

-----
1      char *copy_string(char *s)
2      {
3          int i;
4          char *buffer = (char*)malloc(strlen(s) + 1);
5
6          for (i = 0; s[i] != '\0'; ++i)
7              buffer[i] = s[i];
8
9          return buffer;
10     }
-----

```

FIG. 2A

```

-----
1      char *copy_string(char *s)
2      {
3          int i;
4          char *p; /* EXPANSION CODE */
5          int tmp; /* EXPANSION CODE */
6          tmp = 0; /* EXPANSION CODE */
7          for (p = s; *p != '\0'; ++p) /* EXPANSION CODE */
8              ++tmp; /* EXPANSION CODE */
9          char *buffer = (char*)malloc(tmp + 1);
10
11         for (i = 0; s[i] != '\0'; ++i)
12             buffer[i] = s[i];
13
14         return buffer;
15     }
-----

```

FIG. 2B

```

-----
1      IF (Z.GT.EPS) THEN
2          A=B1
3      ELSE IF (ABS(Z).LE.EPS) THEN
4          A=B2
5      ELSE
6          A=B3
7      END IF
-----

```

FIG. 3A

```

-----
1      IF (Z.GT.EPS) THEN
2          A=B1
3a     ELSE
        IF (Z.GE.0.0) THEN      ! EXPANSION CODE
            TMP = Z             ! EXPANSION CODE
        ELSE                   ! EXPANSION CODE
            TMP = -Z            ! EXPANSION CODE
        END IF                 ! EXPANSION CODE
3b     IF (TMP.LE.EPS) THEN
4          A=B2
5      ELSE
6          A=B3
3c     END IF
7      END IF
-----

```

FIG. 3B

TOP SECRET




FIG. 4




FIG. 5

INPUT: PROGRAM UNIT P

OUTPUT: P' OBTAINED BY AMENDING P, AND PROCEDURE S₁, ..., S_n ($0 \leq n$)




FIG. 6

```

-----
1      PROGRAM SAMPL
2      INTEGER N(100)
3      REAL A(10,20,30),B
      ...
4      B = SUM(A)
5      WRITE(*,*) SUM(N(51:100))
6      END
-----

```

FIG. 7A

```

-----
1      PROGRAM SAMPL
2      INTEGER N(100)
3      REAL A(10,20,30),B
      ...
4      B = SUM_SAMPL_1(A)
5      WRITE(*,*) SUM_SAMPL_2(N(51:100))
6      END
-----

```

FIG. 7B

```

-----
      arg-type FUNCTION SUM(X)
      arg-type X(lb(1):ub(1), ..., lb(m):ub(m))
      SUM = 0
      DO 999 Im = lb(m), ub(m)
        :
      DO 999 I1 = lb(1), ub(1)
        SUM = SUM+X(I1,...,Im)
999  CONTINUE
      RETURN
      END
-----

```

FIG. 8


```

-----
      REAL FUNCTION SUM_SAMPL_1(X)
      REAL X(1:10,1:20,1:30)
      SUM_SAMPL_1 = 0
      DO 999 I3 = 1, 30
      DO 999 I2 = 1, 20
      DO 999 I1 = 1, 10
        SUM_SAMPL_1 = SUM_SAMPL_1+X(I1,I2,I3)
999 CONTINUE
      RETURN
      END
-----

```

FIG. 9A

```

-----
      INTEGER FUNCTION SUM_SAMPL_2(X)
      INTEGER X(51:100)
      SUM_SAMPL_2 = 0
      DO 999 I1 = 51, 100
        SUM_SAMPL_2 = SUM_SAMPL_2+X(I1)
999 CONTINUE
      RETURN
      END
-----

```

FIG. 9B




FIG. 10

INPUT: PROGRAM UNIT P

OUTPUT: P' OBTAINED BY AMENDING P, AND PROCEDURE S1,..., Sm (0 ≤ m ≤ n)




FIG. 11

```

1      PROGRAM SAMPL
2      INTEGER N(100),M(200)
3      REAL A(10,20,30),A2(10,20,30),B
4      ...
5      B = SUM(A)+SUM(A2)
6      WRITE(*,*) SUM(N(51:100))
7      WRITE(*,*) SUM(M(51:200))
8      END

```

FIG. 12A

```

1      PROGRAM SAMPL
2      INTEGER N(100),M(200)
3      REAL A(10,20,30),A2(10,20,30),B
4      ...
5      B = SUM_SAMPL_1(A)+SUM_SAMPL_1(A2)
6      WRITE(*,*) SUM_SAMPL_2(N(51:100))
7      WRITE(*,*) SUM_SAMPL_3(M(51:200))
8      END

```

FIG. 12B

CALL	arg-type	m	lb(1)	ub(1)	lb(2)	ub(2)	lb(3)	ub(3)
SUM_SAMPL_1	REAL	3	1	10	1	20	1	30

FIG. 13A

CALL	arg-type	m	lb(1)	ub(1)	lb(2)	ub(2)	lb(3)	ub(3)
SUM_SAMPL_1	REAL	3	1	10	1	20	1	30
NEWLY EXTRACTED CALL	REAL	3	1	10	1	20	1	30

FIG. 13B

CALL	arg-type	m	lb(1)	ub(1)	lb(2)	ub(2)	lb(3)	ub(3)
SUM_SAMPL_1	REAL	3	1	10	1	20	1	30
NEWLY EXTRACTED CALL	INTEGER	1	51	100	—	—	—	—

FIG. 13C

CALL	arg-type	m	lb(1)	ub(1)	lb(2)	ub(2)	lb(3)	ub(3)
SUM_SAMPL_1	REAL	3	1	10	1	20	1	30
SUM_SAMPL_2	INTEGER	1	51	100	—	—	—	—
NEWLY EXTRACTED CALL	INTEGER	1	51	200	—	—	—	—

FIG. 13D

```

-----
      INTEGER FUNCTION SUM_SAMPL_3(X)
      INTEGER X(51:200)
      SUM_SAMPL_3 = 0
      DO 999 I1 = 51, 200
        SUM_SAMPL_3 = SUM_SAMPL_3+X(I1)
999  CONTINUE
      RETURN
      END
-----

```

FIG. 14

CALL	<i>arg-type</i>	<i>m</i>
SUM(A)	REAL	3
SUM(A2)	REAL	3
SUM(N(51:100))	INTEGER	1
SUM(M(51:200))	INTEGER	1

FIG. 16


```

-----
PROGRAM SAMPL
INTEGER N(100),M(200)
REAL A(10,20,30),A2(10,20,30),B
...
B = SUM_SAMPL_1(A)+SUM_SAMPL_1(A2)
WRITE(*,*) SUM_SAMPL_2(N(51:100))
WRITE(*,*) SUM_SAMPL_2(M(51:200))
END
-----

```

} OBJECT CODE

```

-----
REAL FUNCTION SUM_SAMPL_1(X)
REAL X(:,:,:)
SUM_SAMPL_1 = 0
DO 999 I3 = LBOUND(X,3),UBOUND(X,3)
DO 999 I2 = LBOUND(X,2),UBOUND(X,2)
DO 999 I1 = LBOUND(X,1),UBOUND(X,1)
SUM_SAMPL_1 = SUM_SAMPL_1+X(I1,I2,I3)
999 CONTINUE
RETURN
END
-----

```

} PROCEDURE
CODE A

```

-----
INTEGER FUNCTION SUM_SAMPL_2(X)
INTEGER X(:)
SUM_SAMPL_2 = 0
DO 999 I1 = LBOUND(X,1),UBOUND(X,1)
SUM_SAMPL_2 = SUM_SAMPL_2+X(I1)
999 CONTINUE
RETURN
END
-----

```

} PROCEDURE
CODE B

FIG. 17




FIG. 18

INPUT : FILE F CONTAINING PROGRAM UNIT $P_1, \dots, P_t (1 \leq t)$
 OUTPUT : FILE F' CONTAINING P'_1, \dots, P'_t OBTAINED BY AMENDING P'_1, \dots, P'_t ,
 AND PROCEDURE $S_1, \dots, S_m (0 \leq m \leq n)$




FIG. 19

```
-----  
C-- main program ----  
PROGRAM SAMPL  
INTEGER N(100)  
REAL A(10,20,30),A2(10,20,30),B  
...  
B = SUM(A)  
B = SUM_AND_ADD(A,B)  
WRITE(*,*) SUM(N(51:100))  
END  
C-- subprogram ----  
REAL FUNCTION SUM_AND_ADD(Q,S)  
REAL Q(10,20,30),S  
SUM_AND_ADD = SUM(Q)+S  
RETURN  
END  
C-- end of user programs ----  
-----
```

FIG. 20

```

-----
C-- main program ----
  PROGRAM SAMPL
    INTEGER N(100)
    REAL A(10,20,30),A2(10,20,30),B
    ...
    B = SUM_TINY_1(A)
    B = SUM_AND_ADD(A,B)
    WRITE(*,*) SUM_TINY_2(N(51:100))
    END
C-- subprogram ----
  REAL FUNCTION SUM_AND_ADD(Q,S)
    REAL Q(10,20,30),S
    SUM_AND_ADD = SUM_TINY_1(Q)+S
    RETURN
    END
C-- end of user programs ----

    REAL FUNCTION SUM_TINY_1(X)
    REAL X(1:10,1:20,1:30)
    SUM_TINY_1 = 0
    DO 999 I3 = 1, 30
    DO 999 I2 = 1, 20
    DO 999 I1 = 1, 10
      SUM_TINY_1 = SUM_TINY_1+X(I1,I2,I3)
999 CONTINUE
    RETURN
    END
    } PROCEDURE
    CODE A

    INTEGER FUNCTION SUM_TINY_2(X)
    INTEGER X(51:100)
    SUM_TINY_2 = 0
    DO 999 I1 = 51, 100
      SUM_TINY_2 = SUM_TINY_2+X(I1)
999 CONTINUE
    RETURN
    END
    } PROCEDURE
    CODE B
-----

```

FIG. 21




FIG. 22

INPUT : FILES F_1, \dots, F_s ($1 \leq s$) CONTAINING PROGRAM UNITS P_1, \dots, P_t ($1 \leq t$)
 OUTPUT : FILE F_0 CONTAINING F_1', \dots, F_s' OBTAINED BY AMENDING
 F_1, \dots, F_s , AND PROCEDURES S_1, \dots, S_m ($0 \leq m \leq n$)




FIG. 23

```

FILE tiny1.f:
-----
C-- main program ----
  PROGRAM SAMPL
  INTEGER N(100)
  REAL A(10,20,30),A2(10,20,30),B
  ...
  B = SUM(A)
  B = SUM_AND_ADD(A,B)
  WRITE(*,*) SUM(N(51:100))
  END
C-- end of main program ----
-----
FILE tiny2.f:
-----
C-- subprogram ----
  REAL FUNCTION SUM_AND_ADD(Q,S)
  REAL Q(10,20,30),S
  SUM_AND_ADD = SUM(Q)+S
  RETURN
  END
C-- end of subprogram ----
-----

```

FIG. 24

003363 0410
T04T40 22952860

```
FILE tiny1.o:
-----
C-- main program ----
  PROGRAM SAMPL
    INTEGER N(100)
    REAL A(10,20,30),A2(10,20,30),B
    ...
    B = SUM_1(A)
    B = SUM_AND_ADD(A,B)
    WRITE(*,*) SUM_2(N(51:100))
    END
C-- end of main program ----
-----
FILE tiny2.o:
-----
C-- subprogram ----
  REAL FUNCTION SUM_AND_ADD(Q,S)
    REAL Q(10,20,30),S
    SUM_AND_ADD = SUM_1(Q)+S
    RETURN
    END
C-- end of subprogram ----
-----
FILE onlines.o:
-----
    REAL FUNCTION SUM_1(X)
    REAL X(1:10,1:20,1:30)
    SUM_1 = 0
    DO 999 I3 = 1, 30
    DO 999 I2 = 1, 20
    DO 999 I1 = 1, 10
      SUM_1 = SUM_1+X(I1,I2,I3)
    999 CONTINUE
    RETURN
    END
    } PROCEDURE
    CODE A

    INTEGER FUNCTION SUM_2(X)
    INTEGER X(51:100)
    SUM_2 = 0
    DO 999 I1 = 51, 100
      SUM_2 = SUM_2+X(I1)
    999 CONTINUE
    RETURN
    END
    } PROCEDURE
    CODE B
-----
```

FIG. 25

```

-----
1      SUBROUTINE SUBP(LEN)
2      REAL,PARAMETER :: PAI=3.14159, R=100.0
3      INTEGER LEN,M
4      REAL :: S(2**LEN-1)
5      ...
6      M=PAI*(R*2)**2
7      ...
8      END SUBROUTINE
-----

```

FIG. 26A

```

-----
SUBROUTINE SUBP(LEN)
REAL,PARAMETER :: PAI=3.14159, R=100.0
INTEGER LEN,M
REAL :: S(POW_SUBP_1(2,LEN)-1)
...
M=PAI*POW_SUBP_2((R*2),2)
...
END SUBROUTINE
-----

```

OBJECT PROGRAM

```

-----
FUNCTION POW_SUBP_1(A,N) RESULT(R)
INTEGER A,R
INTEGER N

SELECT CASE (N)
CASE (0)
R=1
CASE (1)
R=A
CASE (2)
R=A*A
CASE (3)
R=A*A*A
CASE DEFAULT
R=A**N
END SELECT
RETURN
END FUNCTION
-----

```

ONLINE CODE A

```

-----
FUNCTION POW_SUBP_2(A,N) RESULT(R)
REAL A,R
INTEGER N

R=A*A
RETURN
END FUNCTION
-----

```

ONLINE CODE B

FIG. 26B

```

-----
FUNCTION name(A,N) RESULT(R)
  arg-type A,R
  INTEGER N

  R=1
  RETURN
END FUNCTION
-----

```

FIG. 27A

```

-----
FUNCTION name(A,N) RESULT(R)
  arg-type A,R
  INTEGER N

  R=A
  RETURN
END FUNCTION
-----

```

FIG. 27B

```

-----
FUNCTION name(A,N) RESULT(R)
  arg-type A,R
  INTEGER N

  R=A*A
  RETURN
END FUNCTION
-----

```

FIG. 27C

```

-----
FUNCTION name(A,N) RESULT(R)
  arg-type A,R
  INTEGER N

  R=A*A*A
  RETURN
END FUNCTION
-----

```

FIG. 27D

FUNCTION *name*(A,N) RESULT(R)
 arg-type A,R
 INTEGER N

 R=A**N
 RETURN
END FUNCTION

FIG. 28A

FUNCTION *name*(A,N) RESULT(R)
 arg-type A,R
 INTEGER N

 SELECT CASE (N)
 CASE (0)
 R=1
 CASE (1)
 R=A
 CASE (2)
 R=A*A
 CASE (3)
 R=A*A*A
 CASE DEFAULT
 R=A**N
 END SELECT
 RETURN
END FUNCTION

FIG. 28B




FIG. 29




FIG. 30